PRODUCT INFORMATION SHEET

COMMISSION DELEGATED REGULATION (EU) 2019/2015

Supplier's name or trade mark:			ALESSI				
Supplier's address			Via Privata Alessi 6 – 28887 Crusinallo di Omegna (VB)				
Model identifier			B12_1,5_81LED				
Type of light source			LED bulb				
Lighting technolog used:		LED	Non-directional or directional:	NDLS			
Mains or non-mai	ns:	NMLS	Connected light source (CLS):	no			
Colour-tuneable light source:		no	Envelope:	no			
High luminance lig source:	ght	no					
Anti-glare shield:		no	Dimmable:	Specific dimmer			
Product paramet	Product parameters						
Parameter		Value	Parameter	Value			
General product parameters							
Energy consumpt on-mode (kWh/1		3	Energy efficiency class	F			
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		275 in sphere	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2700K			
On-mode power (Pon), expressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	-			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84			
Outer	Height	43	Spectral power				
dimensions	Width	18,5	distribution in the range	5,0006-2-			
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	18,5	250 nm to 800 nm, at full-load	\$ 4,000E-2- \$ 3,000E-2- \$ 3,000E-2- \$ 2,500E-2- \$ 2,500E-2- \$ 1,000E-2- \$ 1,000E-3- \$ 1,0			
Claim of equivalent power		-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	x: 0.4245 y: 0.4020			

Parameters for directional light sources:						
Peak luminous intensity (cd)	-	Beam angle in degrees, or the range of beam angles that can be set	360°			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	17	Survival factor	-			
the lumen maintenance factor	-					

Parameters for LED and OLED mains light sources:							
displacement factor (cos	-	Colour consistency in	-				
φ1)		McAdam ellipses					
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replacement claim (W)	-				
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-				