Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | ELEGATED REGUL | ATION (EU) 2019/2 | 015 with regard to energ | gy labelling of light | | |
|--|----------------|---------------------------|--|-----------------------|--|--|
| Supplier's name | or trade mark: | Rosendahl - Soft Sp | ot Solar H34 | | | |
| Supplier's address: Product Development, Slotsmarken 1, 2970 Hørsholm, DK | | | | | | |
| Model identifie | r: 26302 | | | | | |
| Type of light so | urce: | | | | | |
| Lighting technology used: | | LED | Non-directional or directional: | NDLS | | |
| Light source cap-type | | SMD | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-m | ains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | | No | Envelope: | • | | |
| High luminance light source: | | No | | | | |
| Anti-glare shield: | | No | Dimmable: | No | | |
| Product parameters | | | | | | |
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 1 | Energy efficiency class | F | | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 80 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 | | |
| On-mode power (P _{on}), expressed in W | | 1,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,10 | | |
| Networked standby power ($P_{\rm net}$) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 90 | | |
| Outer dimensions without | Height | 34 | Spectral power | See image | | |
| | Width | 23 | distribution in the | in last page | | |
| | Depth | 23 | 1 | | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | |
|--|-------------|---|---|
| Claim of equivalent power ^(a) | | If yes, equivalent power (W) | ā |
| | | Chromaticity coordinates (x and y) | - |
| Parameters for LED and OLED lig | ht sources: | | |
| R9 colour rendering index value - | | Survival factor | • |
| the lumen maintenance factor | - | | |

⁽a)_{'-'} : not applicable;

 $⁽b)_{'-'}$: not applicable;